




PRESSURE-SEAL PISTON CHECK VALVE 900LB~2500LB



Eg. FIG. PC9P 4Y

Features:

Pressure-seal Piston Check Valve 900Lb~2500Lb

Standard Material Specifications

NO.	Part Name	CS to ASTM	AS to ASTM	SS to ASTM	
		Type A105	Type F22	Type F304(L)	Type F316(L)
1	Body	A105	A182 F22	A182 F304(L)	A182 F316(L)
2	Life Disc	A276 420	A276 304	A276 304(L)	A276 316(L)
3	Sealing Seat	A105	F22	A182 F304(L)	F316(L)
4	Pressure Ring	08F	08F	A276 304L	A276 316L
5	Retaining Nut	A194 2H	A194 4	A194 8	A194 8M
6	P.S.Lock Nut	A194 2H	A194 4	A194 8	A194 8M
Suitable Medium		W.O.G.etc	W.O.G.etc	HNO ₃ ,CH ₃ OOH etc	
Suitable Temperature		-29~425	-29~550	-29~180	

Note: Other materials are available upon request.

Dimensions (mm) and Weights (Kg)



NPS		1/2"	3/4"	1"	1-1/4"	1-1/2"	2"
L	900~1500Lb	140	140	140	178	178	216
	250Lb	186	186	186	232	232	279
H		117	117	117	152	152	195
Weights	900~1500Lb	7.5	7.0	6.8	18.5	18.1	20.3
	2500Lb	9.0	7.6	8.4	19.5	20.1	21.8